

*solvent weld seal.

The professional's choice.



KwikRepair™

Do the job with just one fitting.

A new concept in PVC pipe repair and fitting replacement.

- Exceeds ASTM D2466-97 burst pressure requirements for Schedule 40 fittings
- No O-Rings to fail
- Save time
- Replace defective fittings or add to existing systems
- No pipe flexing needed for installation
- Permanent solvent weld seal
- Save significantly on both material and labor costs
- Effective for limited space applications

KwikRepair vs. Telescoping Couplings/Socket Fittings

	KwikRepair tee -vs- ordinary fittings	
Number of fittings required	1	• 4
Number of solvent welds required	3	• 7
Pipe movement restraint required	NO	• YES
Possible O-Ring failure	NO	• YES
Minimum space required to install 1" tee	9-3/4" x 5-1/2"	• 21" x 5-1/2"
*Approximate minutes to install	5-15	• 15-45

Available sizes:


- Couplers. 1/2" through 4"
- Elbows & Tees. 1/2" through 2"

**Depending on accessibility.*

Dawn Industries, Inc.
 5055 W. 58th Avenue Arvada, Colorado 80002
 Phone |303| 296-4041 Fax |303| 295-6604
www.dawnindustries.com |800| 321-7246

Other fine products from Dawn Industries, Inc.

PATENT NO. 6318761



Dawn™