

42 Moving Water!

Filter pumps

Aquamax SF 1000-3500 | Filter pumps

- The difference to other pond pumps is the specially formed impeller that powerfully transports even strongly polluted water via its two large blades
- 2 inlets – 1 outlet
The new Aquamax offers more advantages for garden pond use with its special drive motor. The satellite strainer, included with the product, makes it possible to draw water from a more remote point in the pond and introduce it into the connected filter system.
- The 2nd inlet is adjustable in 4 levels. Alternatively the second input makes it possible to connect a skimmer to transport pond and surface water in the filter system at the same time.
- The motor housings of Aquamax pumps are made of the highest quality composite.
- The large-surface wrap-around strainer allows debris like Koi waste or dead plants up to $\frac{3}{8}$ in. to pass through.
- OASE introduces the first pump that is completely capable of withstanding winter conditions due to new, patent-pending, freeze protection technology. Even if the pump is completely frozen into the pond it will not be damaged.

Aquamax	1000	1600	2200	3000	3500
Max. Flow Rate	1000 gph	1600 gph	2200 gph	3000 gph	3500 gph
Max. Head	90 in.	126 in.	132 in.	186 in.	228 in.
Strainer Surface Area (Pump/Satellite)	147 sq. in. / 100 sq. in.				
Connections	2 in. threaded (1 in. – 1 1/2 in. tubing adapter included)				
Power Consumption	65 W	95 W	138 W	200 W	300 W
Cable Length	20 ft.				
Size (L x W x H)	13.8 x 11.2 x 6.4 in.				
Weight	9.9 lbs		13.3 lbs (6.0 kg)		
Part Number	56923	56924	56925	56927	56928
MSRP	CDN \$ 659.98	CDN \$ 769.98	CDN \$ 899.98	CDN \$ 1099.98	CDN \$ 1199.98

All OASE Aquamax SF pumps operate at **110V/60 Hz**. Aquamax SF pumps are protected by a **5-year limited warranty** (3 years plus 2-year extension upon product registration).

