



Count on it.

T5 Series Rotor

A multi purpose, basic featured rotor for all standard residential and commercial uses.

ROTORS



*Even with more time between cuttings—
One head stands tall!*

Competition
"A"



T5



Competition
"B"



INNOVATIVE

In-ground profile of any standard 4" pop-up, but delivers a full 5" pop-up.

EXTRA PERFORMANCE

Highly engineered nozzles deliver maximum irrigation efficiency from a nozzle tree of 8 Standard and 4 low angle nozzles.

VALUE

Part- and full-circle sprinkler in one head with optional check valve.

TORO**Count on it.**

SPECIFICATIONS

T5 Series

Rotor

**NOZZLES**

Geometry on the face of the nozzle creates breakup.

**STREAM STRAIGHTENERS**

Align the water flow behind the nozzle.

**EXTENSIVE TESTING**

T5 nozzle efficiency was developed using SPACE™ calculations

Features & Benefits**5" Pop-Up**

- Easily replaces many competitive units in the same footprint but delivers an extra inch of pop-up

Standard Rubber Cover

- The top of the sprinkler is covered with a heavy duty rubber cover to minimize impact injuries and reduce liability

Nozzle Tree

- The T5 comes with a full nozzle tree of 8 standard nozzles (25°) and 4 low angle nozzles (10°)

Optional Check Valve

- An optional check valve is available with a hold back strength of 7' of elevation change

Top Adjust Arc Set

- The T5 can be set between a minimum arc set of 40° and a full circle set of 360°
- Arc changes are made from the top of the sprinkler while popped up or down by using a small slotted screwdriver.

Specifications**Model Description**

- T5P 5" Lawn Pop-up w/o check valve

Dimensions

- Body Diameter: 2 1/4"
- Cap Diameter: 2 5/8"
- Height: 7 1/2"

Operating Specifications

- Radius: 25'-50'
- Flow Rate: .76 – 9.63 GPM
- Recommended Operating Pressure Range: 25-65 PSI (maximum – 75 psi)
- Trajectory: 25° standard, 10° low angle
- Pop-up to nozzle: 5"
- Inlet: 3/4" NPT
- Factory installed with a #3.0 nozzle

Options Available

- Check valve

Warranty

- Two years

Specifying Information—T5 Sprinkler

T5P-XXXX-COM-E					
Description	Body	Nozzle		Optional	Effluent
T5P	P	XXXX		COM	E
T5 Sprinkler	P—5" Lawn Pop-up S—Shrub* HP—High-pop* *Available Summer 2008	15—1.5 GPM	Low Angle Nozzle 10LA—1.0 GPM 15LA—1.5 GPM 20LA—2.0 GPM 30LA—3.0 GPM	COM—Check-O-Matic	E—Effluent
		20—2.0 GPM			
		25—2.5 GPM			
		30—3.0 GPM			
		40—4.0 GPM			
		50—5.0 GPM			
		60—6.0 GPM			
		80—8.0 GPM			

Example: A T5 pop-up sprinkler with a 2.5 GPM nozzle, would be specified as: T5P-25

The Toro Company • Irrigation Division • www.toro.com

5825 Jasmine St. Riverside, CA • 92504 • 877.345.8676

P/N 08-1009-IRC • Specifications subject to change without notice. For more information, contact your local Toro distributor. ©2008 The Toro Company.

All rights reserved.