



The **FP Series** pumps are specifically designed for use in pond and water garden filtration systems. These pumps will handle up to 3/8" solids and remove them from the pond which greatly improves overall water quality and reduces maintenance. The FP pumps are specifically designed to deliver high water flow at very low energy consumption. This makes these pumps ideal for continuous operation. Because these pumps use asynchronous technology, the flow rate can be electronically controlled. This means the output is completely adjustable and the pump only uses the power necessary for the desired flow.



*The **FP pumps** are an integral part of the **Clearwater Guarantee**. When sized correctly and used with the proper filtration components, they will guarantee that the pond or water garden will have clear water for a lifetime.*

	FP-1750	FP-2300	FP-3200
Power Consumption (watts)	110	150	200
Max. Flow Rate (gph / gpm)	1750 / 29.2	2300 / 38.3	3200 / 53.3
Max. Head (ft)	10	13	18
Outlet	1 1/2"	1 1/2"	1 1/2"
Power Cable Length (ft)	20	20	20
Dimensions	12"x10"x6"	12"x10"x6"	12"x10"x6"
Warranty	3 Years	3 Years	3 Years

FEATURES

- ★ Solids handling, passes up to 3/8" particles.
- ★ Energy efficient Mag-drive.
- ★ In line Capable.

Pump Performance Chart

	1'	5'	10'	15'
FP-1750	1,750	1,600		
FP-2300	2,250	2,100	1,600	
FP-3200	3,280	3,100	2,650	1,580



Note: For more information on pump performance please refer to the pump curves in the back of the catalog

